



> PRINT > COPY > SCAN > FAX

TASKalfa 8002i

B/W MULTIFUNCTIONAL
FOR A3 FORMAT

THE B/W THAT MEETS THE HIGHEST DEMANDS



This high-performance MFD will astound you: It delivers amazing b/w print results even at the highest print speeds and will benefit the productivity of your office in many ways. With a input paper capacity of 7,650 sheets an output paper capacity of 4,000 sheets, it is well suited for even the largest and most complex print jobs. The convenient paper handling and finishing options allow you to produce complex documents, such as booklets and tri-folded leaflets, in-house. Thanks to its newly designed 9" touch panel, accessing all features and getting exactly the results you need, is very intuitive and simple.

- > Up to 80 A4 ppm in b/w
- > Outstanding image quality due to advanced imaging technology
- > Standard print resolution of 1,200 x 1,200 dpi
- > State-of-the-art 4.5 GB RAM + 8 GB SSD + 320 GB HDD
- > Long-life components providing exceptional efficiency and reliability
- > Individual paper handling options, including booklet and tri-folding
- > Standard network and mobile printing, as well as colour scanning
- > Comprehensive security functions.



The TASKalfa 8002i incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 8002i provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.

TASKalfa 8002i GENERAL

Technology

KYOCERA Laser Monochrome, HyPAS™ solution platform

Engine speed (pages per minute): Up to 80/40 ppm A4/A3

Resolution: 1,200 x 1,200 dpi, 2-bit depth for print quality of 4,800 dpi equivalent x 1,200 dpi

Warm-up time from power on: Approx. 30 seconds or less

Time to first page: Approx. 4.7 seconds or less

CPU: Freescale QorIQ T1042 Quad Core 1.2 GHz

Memory: 4.5 GB RAM + 8 GB SSD + 320 GB HDD **Standard**

interfaces: USB 2.0 (Hi-Speed) x4, USB Host 2.0, Fast Ethernet 10BaseT/100BaseTX/1000BaseT, slot for optional print server, slot for optional SD, SDHC card, slot for optional fax system

Dimensions (W x D x H) – main unit

750 x 822 x 1234 mm (DP, operation panel included) **Weight:**

Main unit approx. 150 kg

Power source: AC 220 V ~ 240 V, 50/60 Hz

Power consumption

Printing: 1,170 W

Ready mode: 100 W

Sleep mode: 1 W or less

Noise (sound pressure level ISO 7779/ISO 9296)

Printing: 75dB(A)(Lwad)

Ready mode: 58dB(A)(Lwad)

Safety standards: IEC60950-1, IEC60825-1; This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard. RoHS compatibility

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 150-sheet multi-purpose tray, 60 – 300 g/m²

(banner 136 – 165 g/m²), A6R – 305 x 457 mm, banner max.

305 x 1,220 mm; 2x 1,500-sheet high-capacity paper deck,

60 – 256 g/m², A4, B5; 2x 500-sheet universal paper

cassette, 60 – 256 g/m², A5R – 305 x 457 mm incl. custom

paper sizes; Max. input capacity with options: 7,650 sheets A4

Document processor: (one-path duplex scanning) 270

sheets; 35 – 220 g/m² (simplex), 50 – 220 g/m² (duplex);

A6R – Banner up to 2,200 mm

Duplex unit: Duplex as standard supports A5R – 305 x 457

mm, 60 – 256 g/m²

Output capacity

Standard job separator tray 70 sheets, optional copy tray

(D): upper 100 sheets, lower 250 sheets; max. optional

output capacity 4,300 sheets

PRINT FUNCTIONS

Controller language: PRESCRIBE

Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3

compatible), PDF Direct Print, XPS Direct Print and OpenXPS

Operating systems: All current Windows operating systems, Mac OS X Version 10.8 or higher, UNIX, LINUX, as well as other operating systems on request.

Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, Private Print, job storage and job management functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google Cloud Print

COPY FUNCTIONS

Max. original size: A3

Continuous copying: 1 – 9999

Zoom range: 25 – 400% in 1% steps

Preset magnification ratios: 5R/5E

Digital features: Scan once copy many, electronic sort, 2-in-1 and 4-in-1 function, image repeat copy, page numbering, cover mode, booklet copy, interrupt copy, form overlay, stamp function and skip-blank-page function.

Exposure mode: Auto, manual: 16 steps

Image adjustments: Text + photo, text, photo, map

SCAN FUNCTIONS

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB, Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scan

Scan speed: (A4, 300 dpi, Dual Scan) 220 images per minute

Scan resolution: 600 x 600 dpi, 400 x 400 dpi, 300 x

300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi (24 bit)

Max. scan size: A3, Banner up to 2,200 mm

Original recognition: Text, photo, text + photo, optimised for OCR

File types: PDF (high compression, encrypted, PDF/A),

Searchable PDF (OCR), JPEG, TIFF, XPS, OpenXPS

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3

Modem speed: Max. 33.6 kbps

Transmission speed: Max. 3 seconds (JBIG)

Fax resolution:

Normal: 200 x 100 dpi

Fine: 200 x 200 dpi

Superfine: 200 x 400 dpi

Ultrafine: 400 x 400 dpi

600 x 600 dpi

Maximum original size: A3, Banner up to 1,600 mm

Compression method: JBIG, MMR, MR, MH

Features: Opt. Internet-fax, network faxing, rotate trans-

mission, rotate reception, duplex fax reception, memory

reception, mailbox, remote diagnostics, dual fax with

second fax system 12

CONSUMABLES

TK-672g Toner-Kit: Average continuous toner yield 70,000 pages in accordance with 5% coverage A4

WT-861 Waste Toner Bottle

600,000 sheets (in accordance with 5% coverage)

Staple cartridge: SH-10 for BF-730, SH-12 for DF-7110

OPTIONS

Fax System 12

Internet Fax Kit (A)

Paper handling

PF-730(B) Paper feeder

2x 500 sheets, 60 – 256 g/m², A5R – 305 x 457 mm, folio

PF-740(B) Paper feeder

2x 1,500 sheets, 60 – 256 g/m², A4, B5, letter

PF-7130 Paper feeder

500 sheets, 60 – 256 g/m², A5R – 305 x 457 mm

PF-7120 A4 side deck: 3,000 sheets, 60 – 256 g/m², A4, B5

DF-7110 Document finisher

Main tray: max. 4,000 sheets A4 (3,000 sheets with BF-730

attachment); max. 60 – 300 g/m²; max. B5R – 305 x 457 mm

Sub-tray: 200 sheets A4; 60 – 300 g/m²; A6R – 305 x 457 mm

Sub-tray (top): 100 sheets; 60 – 300 g/m²; A6R – A4

Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions,

B5 – 305 x 457 mm

PH-7C Punch unit for DF-7110

2-hole/4-hole/60 – 300 g/m², A5R – A3

MT-730(B) Mailbox sorter for DF-7110

7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 163 g/m²

BF-730 Booklet and tri-folding unit for DF-7110

Half folding: 60 – 256 g/m², A3, B4, A4R

Booklet: max. 16 sheets (64 pages, 60 – 90 g/m²)

Non-staple folding: max. 5 sheets (60 – 90 g/m²)

Tri-folding: 60 – 105 g/m², A4R

Multi tri-folding: 5 sheets (60 – 90 g/m²), 3 sheets

(91 – 105 g/m²)

Copy tray (D): upper tray 100 sheets, lower tray 250 sheets

Banner Guide (A): Banner paper feeding guide, up to 10 sheets

Security

Data Security Kit (E): In line with ISO 15408 (Common

Criteria) with security level EAL3

USB IC Card Reader: Card Authentication Kit (B)

Keyboardholder 10

Numeric keypad: NK-7100

UG-33 AC: ThinPrint support

UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850)

Optional interface

IB-35: Direct Wi-Fi Interface

IB-50: Gigabit-Ethernet board

10BaseT/100BaseTX/1000BaseT

IB-51: Wireless Lan Interface



KYOCERA Document Solutions Australia
Ph: 13 59 62
www.kyoceradocumentsolutions.com.au

KYOCERA Document Solutions New Zealand*
Ph: 0800 459 623
www.kyoceradocumentsolutions.co.nz

* KYOCERA Document Solutions New Zealand is the trading name of the New Zealand branch of KYOCERA Document Solutions Australia Pty Ltd a corporation incorporated in Australia.

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERA Document Solutions Australia Pty. Ltd ABN 77 003 852 444

YOUR KYOCERA BUSINESS PARTNER

 **KYOCERA**
Document Solutions